

# JCB ROUGH TERRAIN FORKLIFT TRUCKS

## 926 4WD JCB ECOMAX STAGE IIIB/T4F

### (2014 AND AFTER)



**ENGINE** JCB Ecomax T4f (SCR)  
Capacity: 14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Armado Synth LSP Ultra 5W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Check every 10 hours, change every 500 hours/ 6 months*

**DIFFERENTIAL FRONT**  
Capacity: 30 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

**DIFFERENTIAL REAR**  
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

**HUB REDUCTIONS REAR**  
Capacity: 1 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

**TRANSMISSION** SynchroShuttle  
Capacity: 18 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 10 hours, change every 1000 hours/ 12 months*

# JCB ROUGH TERRAIN FORKLIFT TRUCKS

## 926 4WD JCB ECOMAX STAGE IIIB/T4F

### (2014 AND AFTER)



#### HYDRAULIC SYSTEM

Capacity: 64 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

Check every 10 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 32</b>	<b>Perlus AF 32</b>	

Check every 10 hours, change every 2000 hours/ 24 months

#### HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 15</b>		

Check every 10 hours, change every 2000 hours/ 24 months

#### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	

#### COOLING SYSTEM

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.