

# JCB TELESCOPIC HANDLERS (USA)

## LOADALL/AGRI 540-140 USA (55 KW)

### STAGE IIIB/T4I (2014 AND AFTER)



**ENGINE** JCB Ecomax T4i  
Capacity: 15 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Armado Synth MSP 5W-40**

*Check every 10 hours, change every 500 hours/ 6 months*

**DIFFERENTIAL FRONT**  
Capacity: 17,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 6 months/ 500 hours*

**DIFFERENTIAL REAR**  
Capacity: 19 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 6 months/ 500 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 1,9 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 6 months/ 500 hours*

**HUB REDUCTIONS REAR**  
Capacity: 2 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 6 months/ 500 hours*

# JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 540-140 USA (55 KW) STAGE IIIB/T4I (2014 AND AFTER)

**TRANSMISSION POWERSHIFT PS750**

Capacity: 17 liter (Change capacity), Capacity: 19 liter (Dry fill)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 10 hours, change every 1000 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 10 hours, change every 1000 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 131 liter (Hydraulic tank)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

## PRODUCT RECOMMENDATION 2

**Perlus H 46***Check every 50 hours, change every 2000 hours/ 24 months***HYDRAULIC BRAKE SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Perlus H 15***Check every 10 hours, change every 2000 hours/ 24 months***GREASE POINTS/NIPPLES**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease**

## PRODUCT RECOMMENDATION 2

**Labora Grease**

# JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 540-140 USA (55 KW) STAGE IIIB/T4I (2014 AND AFTER)

**COOLING SYSTEM**

Capacity: 28 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 10 hours, change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*