

JCB TELESCOPIC HANDLERS 540-140 (TILL 2008)

**ENGINE**

Capacity: 12-15,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 2****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 3****Armado Synth 5W-30****DIFFERENTIAL FRONT**

Capacity: 17,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT****DIFFERENTIAL REAR**

Capacity: 19 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT****HUB REDUCTIONS FRONT**

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT****HUB REDUCTIONS REAR**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT**

JCB TELESCOPIC HANDLERS 540-140 (TILL 2008)

**TRANSMISSION Powershift**

Capacity: 21 liter, Capacity: 17 liter (4-speed + SC engine), Capacity: 19 liter (4-speed + SC engine, initial fill), Capacity: 23 liter (Initial fill)

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

HYDRAULIC SYSTEM

Capacity: 131 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 46		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

JCB TELESCOPIC HANDLERS 540-140 (TILL 2008)

**COOLING SYSTEM**

Capacity: 11 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12****PRODUCT RECOMMENDATION 3****Coolant -38 Organic NF**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.