

# JCB WHEELED LOADERS 446 ZX 1181000-> (2001-2005)

**ENGINE**

Capacity: 18,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 2****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 3****Dieselfleet CD+ 15W-40***Check every 10 hours, change every 500 hours***USE**

Initial service

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 2****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 3****Dieselfleet CD+ 15W-40***Check every 10 hours, change every 100 hours***DIFFERENTIAL FRONT**

Capacity: 51 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Check every 100 hours, change every 1000 hours***DIFFERENTIAL REAR**

Capacity: 41 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Check every 100 hours, change every 1000 hours***TRANSMISSION Powershift**

Capacity: 34 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol***Check every 100 hours, change every 1000 hours*

# JCB WHEELED LOADERS 446 ZX 1181000-> (2001-2005)



## HYDRAULIC SYSTEM

Capacity: 215 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32***Check every 10 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease***Change every 100 hours*

## COOLING SYSTEM

Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Check every 10 hours, change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.