

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX016-4 KUBOTA D782-E-BH

### (S/N <- 63626) (2011-2018)



**ENGINE** Kubota D782-E  
Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 10 hours, change every 500 hours*

#### HYDRAULIC SYSTEM

Capacity: 15,5 liter (Hydraulic tank), Capacity: 28 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 1000 hours*

USE	CLIMATE
Breaker use < 40%	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 800 hours*

USE	CLIMATE
Breaker use 40 - 60%	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 400 hours*

USE	CLIMATE
Breaker use 60 - 80%	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 300 hours*

USE	CLIMATE
Breaker use > 80%	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 200 hours*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX016-4 KUBOTA D782-E-BH

### (S/N <- 63626) (2011-2018)

**COOLING SYSTEM**

Capacity: 2,7-2,9 liter, Capacity: 0,56 liter (Reserve tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 24 months***IDLER FRONT**

Capacity: 0,03 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 2000 hours***TRACK ROLLER**

Capacity: 0,04 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 2000 hours***TRAVEL REDUCTION UNIT**

Capacity: 0,33 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

*Change every 500 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

*Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.