

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX080-3 KUBOTA V3307DI-TE3

### (TIER 4I) (2007-2013)



**ENGINE** Kubota V3307-DI-TE3  
Capacity: 10,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Change every 500 hours*

**HYDRAULIC SYSTEM**  
Capacity: 146 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Change every 1000 hours*

#### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

**COOLING SYSTEM**  
Capacity: 8,2 liter (Radiator), Capacity: 1,3 liter (Reserve tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 24 months*

**IDLER FRONT**  
Capacity: 0,08 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 2000 hours*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX080-3 KUBOTA V3307DI-TE3

### (TIER 4I) (2007-2013)

**TRACK ROLLER**

Capacity: 0,08 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 2000 hours***TRAVEL REDUCTION UNIT**

Capacity: 1,03 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

**UPPER ROLLER**

Capacity: 0,06 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.