

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX41-2C KUBOTA D1105-BH

### (1997-1998)


**ENGINE** Kubota D1105

| USE                           |                               | CLIMATE                  |
|-------------------------------|-------------------------------|--------------------------|
| Normal                        |                               | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SCD 50</b> |

*Check every 8 hours, change every 250 hours*

| USE                          |                           | CLIMATE |
|------------------------------|---------------------------|---------|
| Normal                       |                           | Cold    |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2  |         |
| <b>Multifleet SCD 20W-20</b> | <b>Multifleet SCD 10W</b> |         |

*Check every 8 hours, change every 250 hours*

| USE                           |                               | CLIMATE                  |
|-------------------------------|-------------------------------|--------------------------|
| Initial service               |                               | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SCD 50</b> |

*Change every 50 hours*

| USE                          |                           | CLIMATE |
|------------------------------|---------------------------|---------|
| Initial service              |                           | Cold    |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2  |         |
| <b>Multifleet SCD 20W-20</b> | <b>Multifleet SCD 10W</b> |         |

*Change every 50 hours*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX41-2C KUBOTA D1105-BH

### (1997-1998)

**HYDRAULIC SYSTEM**

Capacity: 22 liter (Hydraulic tank)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 68</b>       |  |  |

*Check every 10 hours, change every 1000 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 46</b>       |  |  |

*Check every 10 hours, change every 1000 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 32</b>       |  |  |

*Check every 10 hours, change every 1000 hours***COOLING SYSTEM**

Capacity: 4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |  |
|-------------------------------|--------------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |  |

*Check every 10 hours, change every 24 months***PINS + BUSHINGS**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
|--------------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Check every 8 hours***SWING REDUCTION UNIT**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Change every 1000 hours*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX41-2C KUBOTA D1105-BH

### (1997-1998)



#### TRACK ROLLERS + FRONT IDLERS

| USE                            |                                    | CLIMATE  |
|--------------------------------|------------------------------------|----------|
| Normal                         |                                    | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b>    | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |
| <i>Change every 1000 hours</i> |                                    |          |

#### TRAVEL REDUCTION UNIT

Capacity: 0,25 liter

| USE                                      |                                    | CLIMATE  |
|------------------------------------------|------------------------------------|----------|
| Normal                                   |                                    | Moderate |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b>              | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |
| <i>Change every 500 hours/ 12 months</i> |                                    |          |

| USE                           |                                    | CLIMATE  |
|-------------------------------|------------------------------------|----------|
| Initial service               |                                    | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b>   | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |
| <i>Change every 100 hours</i> |                                    |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.