

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U U27-4 KUBOTA D1105-E4-BH-2

### (2014 AND AFTER)



**ENGINE** Kubota D1105-E4B  
Capacity: 3,6 liter

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Asyntho 5W-30</b>	<b>Armado Synth 5W-30</b>

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 20W-20</b>	<b>Multifleet SCD 10W</b>	

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Normal, fuel sulfur level 0,5 % - 1 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Asyntho 5W-30</b>	<b>Armado Synth 5W-30</b>

*Check every 8 hours, change every 250 hours*

USE	CLIMATE
Normal, fuel sulfur level 0,5 % - 1 %	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 20W-20</b>	<b>Multifleet SCD 10W</b>	

*Check every 8 hours, change every 250 hours*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U U27-4 KUBOTA D1105-E4-BH-2

### (2014 AND AFTER)

**HYDRAULIC SYSTEM**

Capacity: 22 liter (Service fill), Capacity: 37,5 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Perlus H 46</b>	<b>Perlus H 68</b>	<b>Perlus AF 46</b>

*Check every 10 hours, change every 1000 hours*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 32</b>	<b>Perlus AF 32</b>	

*Check every 10 hours, change every 1000 hours*

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		

*Check every 10 hours, change every 1000 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>

**COOLING SYSTEM**

Capacity: 0,6 liter (Expansion tank), Capacity: 3-3,2 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 11</b>		

*Check every 10 hours, change every 24 months*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U U27-4 KUBOTA D1105-E4-BH-2

### (2014 AND AFTER)

**TRAVEL REDUCTION UNIT**

Capacity: 0,35 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 10 hours, change every 500 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 50 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*