MANITOU MANISCOPIC MRT MRT 2150 PRIVILEGE E3 MERCEDES-BENZ OM904LA (<- 413079)



ENGINE Mercedes-Benz OM904LA
Capacity: 15 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
01 1 0501	10 11 10001	<u>'</u>

Check every 250 hours, change every 12 months/900 hours

Check every 250 hours, change every 12 months/ 900 hours

DIFFERENTIAL REAR Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HUB REDUCTIONS FRONT Capacity: 1,6 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change eve	ery 12 months/ 900 hours	

HUB REDUCTIONS REAR Capacity: 1,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change eve	erv 12 months/ 900 hours	

MANITOU MANISCOPIC MRT MRT 2150 PRIVILEGE E3 MERCEDES-BENZ OM904LA



(<- 413079)

TRANSMISSION HYDROSTATIC 2/2 Capacity: 2,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 12 months/900 hours

HYDRAULIC SYSTEM HYDROSTATIC DRIVE Capacity: 210 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 50 hours, change every	12 months/ 900 hours	-

GREASE POINTS/NIPPLES GENERAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours	1	'

GREASE POINTS/NIPPLES SLEWING GEAR TOOTHING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours	·	

GREASE POINTS/NIPPLES TELESCOPIC BOOM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Change every 50 hours	,	,	

MANITOU MANISCOPIC MRT MRT 2150 PRIVILEGE E3 MERCEDES-BENZ OM904LA (<- 413079)



COOLING SYSTEM
Capacity: 18 liter

USE

Normal

PRODUCT RECOMMENDATION 2

Coolant SP 15+

Coolant SP 12

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

Check every 10 hours, change every 2700 hours

SWING REDUCTION UNIT Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP HD 150	Abacot MEP 150	
		

Check every 250 hours, change every 12 months/900 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.