

| ENGINE<br>Capacity: 9,4 liter |                          |                          |
|-------------------------------|--------------------------|--------------------------|
| USE                           |                          | CLIMATE                  |
| Normal                        |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40        | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |
| Change every 500 hours        |                          | ·                        |
| USE                           |                          | CLIMATE                  |
| Initial service               |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40        | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |
| Change every 50 hours         |                          |                          |

| ANGLE GEARBOX Capacity: 2,5 liter |                             |          |  |
|-----------------------------------|-----------------------------|----------|--|
| USE                               |                             | CLIMATE  |  |
| Normal                            |                             | Moderate |  |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    |          |  |
| Gearlube GL-5 80W-90              | Unigear HS GL-3/GL-5 80W-90 |          |  |
| Change every 500 hours            | ·                           | ·        |  |
| USE                               |                             | CLIMATE  |  |
| Initial service                   |                             | Moderate |  |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    |          |  |
| Gearlube GL-5 80W-90              | Unigear HS GL-3/GL-5 80W-90 |          |  |
| Change every 50 hours             |                             |          |  |

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |



| <b>DIFFERENTIAL FRONT</b> Capacity: 7,3 liter |          |
|---|----------|
| USE   | CLIMATE  |
| Normal  | Moderate |
| PRODUCT RECOMMENDATION 1                      |          |
| Agrifluid HT                                  |          |
| Change every 500 hours                        |          |
| USE   | CLIMATE  |
| Initial service                               | Moderate |
| PRODUCT RECOMMENDATION 1                      |          |
| Agrifluid HT                                  |          |
| Change every 50 hours                         |          |
|   |          |
| DIFFERENTIAL REAR                             |          |
| Capacity: 7,3 liter                           |          |
| USE   | CLIMATE  |
| Normal  | Moderate |
| PRODUCT RECOMMENDATION 1                      |          |

| USE                      | CLIMATE  |
|--------------------------|----------|
| Initial service          | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Agrifluid HT             |          |
| Change every 50 hours    | <u>'</u> |

| HUB REDUCTIONS FRONT<br>Capacity: 1,65 liter |                             |          |
|--|-----------------------------|----------|
| USE  |                             | CLIMATE  |
| Normal                                       |                             | Moderate |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                         | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 1000 hours                      | ,                           |          |

| use<br>Initial service   |                             | climate<br>Moderate |
|--------------------------|-----------------------------|---------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |                     |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |                     |
| Change every 50 hours    |                             |                     |

**Agrifluid HT** 

Change every 500 hours



| HUB REDUCTIONS REAR<br>Capacity: 1,65 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal                                      |                             | Moderate |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                        | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 1000 hours                     | ·                           |          |
| USE   |                             | CLIMATE  |
| Initial service                             |                             | Moderate |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                        | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 50 hours                       |                             |          |

| TRANSMISSION Capacity: 9,4 liter |          |  |
|----------------------------------|----------|--|
| USE                              | CLIMATE  |  |
| Normal                           | Moderate |  |
| PRODUCT RECOMMENDATION 1         |          |  |
| ATF Almirol                      |          |  |
| Change every 1000 hours          |          |  |
| USE                              | CLIMATE  |  |
| Initial service                  | Moderate |  |
| PRODUCT RECOMMENDATION 1         |          |  |
| ATF Almirol                      |          |  |
| Change every 50 hours            |          |  |

| HYDRAULIC SYSTEM<br>Capacity: 120 liter (Tank) |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                       |          |
| Perlus H 46                                    |          |
| Change every 1000 hours/ 12 months             |          |



| HYDRAULIC BRAKE SYSTEM             |          |  |
|------------------------------------|----------|--|
| USE                                | CLIMATE  |  |
| Normal                             | Moderate |  |
| PRODUCT RECOMMENDATION 1           |          |  |
| LHM +                              |          |  |
| Change every 1000 hours/ 12 months |          |  |

| GREASE POINTS/NIPPLES OTHERS |                          |                          |
|------------------------------|--------------------------|--------------------------|
| USE                          |                          | CLIMATE                  |
| Normal                       |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease                | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| LONGITUDINAL STABILITY ALARM DEVICE REAR |                          |                          |
|--|--------------------------|--------------------------|
| USE                                      |                          | CLIMATE                  |
| Normal                                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease                            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| STABILIZERS CHASSIS      |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |
| Change every 50 hours    | ,                        | '                        |

| COOLING SYSTEM Capacity: 17 liter |                          |                          |
|-----------------------------------|--------------------------|--------------------------|
| USE                               |                          | CLIMATE                  |
| Normal                            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+                    | Coolant SP 12            | Coolant -38 Organic NF   |



| JIB                      |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |
| Change every 50 hours    | •                        | •                        |

| SLIDING PADS JIB         |                           |                          |  |
|--------------------------|---------------------------|--------------------------|--|
| USE                      |                           | CLIMATE                  |  |
| Normal                   |                           | Moderate                 |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |  |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2   | Q5 MP Calcep Grease EP 2 |  |
| Change every 10 hours    | Guilpiox II D Giodos El E |                          |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.