## MANITOU MANISCOPIC MT/MTA MT 431 CP TURBO



	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	

Change every 150 hours

<b>DIFFERENTIAL FRONT</b> Hurth Capacity: 8,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Change every 900 hours	'	'

DIFFERENTIAL REAR
Capacity: 7 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

Change every 900 hours

Capacity: 7 liter

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

HUB REDUCTIONS FRONT Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 900 hours		

HUB REDUCTIONS REAR Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 900 hours		,

## MANITOU MANISCOPIC MT/MTA MT 431 CP TURBO



TRANSMISSION Borg Warner Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	ATF Dexron II-D	
Change every 900 hours		

HYDRAULIC SYSTEM
Capacity: 73 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

Change every 900 hours

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

COOLING SYSTEM Capacity: 15 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

## MANITOU MANISCOPIC MT/MTA MT 431 CP TURBO



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.