MANITOU MANISCOPIC MT/MTA MT 450 CP



| | CLIMATE |
|--------------------------|---------------|
| | Mediterranean |
| PRODUCT RECOMMENDATION 2 | |
| Multifleet SHPD 15W-40 | |
| | |

Change every 150 hours

| DIFFERENTIAL FRONT Capacity: 15 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 900 hours | ' | • |

| DIFFERENTIAL REAR Capacity: 15 liter | | |
|--------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 900 hours | ' | ' |

| HUB REDUCTIONS FRONT Capacity: 1 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 900 hours | | |

| HUB REDUCTIONS REAR Capacity: 1 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 900 hours | · | |

MANITOU MANISCOPIC MT/MTA MT 450 CP



| TRANSMISSION Clark 18000 Capacity: 18 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 10W | ATF Dexron II-D | |
| Change every 900 hours | , | |

| HYDRAULIC SYSTEM Capacity: 180 liter | |
|--------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |
| Change every 900 hours | |

| HYDRAULIC BRAKE SYSTEM | | | |
|---------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |

| | CLIMATE |
|--------------------------|--------------------------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| | |

| COOLING SYSTEM Capacity: 17,5 liter | | | |
|-------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| | | | |

MANITOU MANISCOPIC MT/MTA MT 450 CP



| HYDRAULIC INCHING SYSTEM | | |
|---------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

| TELESCOPIC BOOM | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| MoS2 Grease EP 2 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.