

# MANITOU MANISCOPIC MT/MTA MT 840 SCP



## ENGINE

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

### PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Change every 300 hours*

### USE

Initial service

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

### PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Change every 50 hours*

## AXLE ARTICULATIONS WITH WIELAND BUSHINGS

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## DIFFERENTIAL FRONT

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Agrifluid HT***Change every 900 hours*

## DIFFERENTIAL REAR

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Agrifluid HT***Change every 900 hours*

# MANITOU MANISCOPIC MT/MTA MT 840 SCP



## HUB REDUCTIONS FRONT

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 900 hours*

## HUB REDUCTIONS REAR

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 900 hours*

## TRANSMISSION

| USE                       |                          | CLIMATE  |
|---------------------------|--------------------------|----------|
| Normal                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| <b>Gear Oil Alcat 10W</b> | <b>ATF Dexron II-D</b>   |          |

*Change every 900 hours*

## HYDRAULIC SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus H 46</b>       |  |          |

*Change every 900 hours*

## HYDRAULIC BRAKE SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>LHM +</b>             |  |          |

# MANITOU MANISCOPIC MT/MTA MT 840 SCP



## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## TELESCOPIC JIB PADS

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

## WINCH BRAKE OIL TANK

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus H 46</b>       |  |          |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*