

MANITOU MANISCOPIC MT/MTA MT 930 S

CUMMINS 4B 3.9T

**ENGINE** Cummins 4B3.9T

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 300 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

AXLE ARTICULATIONS WITH WIELAND BUSHINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

DIFFERENTIAL FRONT Hurth

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 900 hours

DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 900 hours

MANITOU MANISCOPIC MT/MTA MT 930 S

CUMMINS 4B 3.9T



HUB REDUCTIONS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 900 hours

HUB REDUCTIONS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 900 hours

TRANSMISSION Spicer Compact Shuttle

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

Change every 900 hours

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 900 hours

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

MANITOU MANISCOPIC MT/MTA MT 930 S

CUMMINS 4B 3.9T



GREASE POINTS/NIPPLES		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

TELESCOPIC JIB PADS		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.