

MANITOU MANITRANSIT RANGE

TMD/TME/TMP/TMT/TMV TMT 55 FL XT-4W

SERIES 1-E2 PERKINS 404C-22



ENGINE Perkins 404C-22
Capacity: 10 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|------------------------------|-------------------------------|-------------------------------|
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |

Check every 10 hours, change every 500 hours/ 12 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|---------------------------|-------------------------------------|
| Synfleet SHPD 10W-40 | Armado Synth 5W-30 | Dieselfleet LSP Ultra 10W-30 |

Check every 10 hours, change every 500 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 31 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 46 | | |

Check every 50 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES GENERAL

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| MoS2 Grease EP 2 | | |

COOLING SYSTEM

Capacity: 11 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------|--|--|
| Coolant -38 Organic NF | | |

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.