

BOMBARDIER OUTLANDER OUTLANDER

400 H.O. (XT) 4 X 4 (2004-2004)

**ENGINE**

Capacity: 2,5 liter

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50***Change every 1500 km/ 50 hours***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-40***Change every 1500 km/ 50 hours***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Helar 0W-40***Change every 1500 km/ 50 hours***USE**

Initial service

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50***Change every 300 km/ 10 hours***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-40***Change every 300 km/ 10 hours***USE**

Initial service

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Helar 0W-40***Change every 300 km/ 10 hours*

BOMBARDIER OUTLANDER OUTLANDER

400 H.O. (XT) 4 X 4 (2004-2004)

**DIFFERENTIAL FRONT**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Check every 1500 km/ 50 hours, change every 6000 km/ 24 months/ 200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Check every 300 km/ 10 hours

DIFFERENTIAL REAR

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Check every 1500 km/ 50 hours, change every 6000 km/ 24 months/ 200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Change every 300 km/ 10 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 6000 km/ 24 months/ 200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 300 km/ 10 hours

BOMBARDIER OUTLANDER OUTLANDER

400 H.O. (XT) 4 X 4 (2004-2004)

**COOLING SYSTEM**

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 6000 km/ 24 months/ 200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.