## **KAWASAKI KLE KLE 500 KLE500-A** (1991-2004)



ENGINE/TRANSMISSION Capacity: 3,4 liter, Filter capacity: 0,4 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		

Check every 3000 km, change every 10000 km/ 12 months

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 20000 km/24 months	'			

GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2			
Change every 20000 km	'	'		

COOLING SYSTEM Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	
Change every 30000 km/24 months	·

FRONT FORK Capacity: 0,52 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 10	
Change every 30000 km/ 36 months	

## PRODUCT RECOMMENDATION

## **KAWASAKI KLE KLE 500 KLE500-A** (1991-2004)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.