

## YAMAHA XJ DIVERSION XJ 900 (1987-1994)



## ENGINE/TRANSMISSION

Capacity: 2,8 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Expulsa RR 15W-50</b> | <b>HDX 15W-40</b>        | <b>HDX 20W-50</b>        |

Change every 6000 km/ 6 months

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Cold                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Expulsa RR 10W-40</b> | <b>Expulsa 10W-40</b>    | <b>HDX 10W-40</b>        |

Change every 6000 km/ 6 months

## SHAFT DRIVE

Capacity: 0,2 liter

| USE                      |                          | CLIMATE                     |
|--------------------------|--------------------------|-----------------------------|
| Normal                   |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> | <b>Gearlube GL-4 80W-90</b> |

Check every 6000 km, change every 24000 km/ 24 months

## HYDRAULIC BRAKE SYSTEM

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Check every 6000 km/ 6 months, change every 24 months

## FRONT FORK

Capacity: 0,28 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Fork Oil RR 5</b>     |  |          |

Check every 6000 km, change every 12000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.