ACURA (USA / CAN) TL UA8, UA9 TL 3.5 (2012-2014)



ENGINE J35Z6 Capacity: 5 liter (Dry fill), Capacity: 4,3 liter (Service)	e fill)
USE	CLIMATE
Flexible (on board maintenance system)	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 0W-20	
TRANSAXLE AUTOMATIC 6/1 Capacity: 7,1 liter (Initial fill), Capacity: 3,1 liter (Se	ervice fill)
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
COOLING SYSTEM	
Capacity: 8,3 liter (Dry fill), Capacity: 6,3 liter (Serv	rice fill)
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.