

# ALFA ROMEO (EU) 145 930 145 1.4 (1994-1997)



## MOTOR

Capacidad: 4 litro

| USO    | CLIMA    |
|--------|----------|
| Normal | Templado |

| RECOMENDACIÓN DE PRODUCTOS 1 | RECOMENDACIÓN DE PRODUCTOS 2 |
|------------------------------|------------------------------|
| <b>Emperol Racing 10W-60</b> | <b>Emperol 10W-40</b>        |

Comprobar cada cada 500 km, cambiar cada cada 20000 km/ 12 meses

| USO    | CLIMA  |
|--------|--------|
| Normal | Ártico |

| RECOMENDACIÓN DE PRODUCTOS 1 | RECOMENDACIÓN DE PRODUCTOS 2 |
|------------------------------|------------------------------|
| <b>Duranza LSP 5W-30</b>     | <b>Asyntho 5W-30</b>         |

Comprobar cada cada 500 km, cambiar cada cada 20000 km/ 12 meses

## TRANSMISIÓN 'TRANSAXLE' MANUAL 5/1

Capacidad: 2,4 litro

| USO    | CLIMA    |
|--------|----------|
| Normal | Templado |

| RECOMENDACIÓN DE PRODUCTOS 1 | RECOMENDACIÓN DE PRODUCTOS 2 |
|------------------------------|------------------------------|
| <b>Gearlube GL-5 80W-90</b>  |                              |

Comprobar cada cada 40000 km, cambiar cada cada 120000 km

## SISTEMA HIDRÁULICO FRENOS Y EMBRAGUE

| USO    | CLIMA    |
|--------|----------|
| Normal | Templado |

| RECOMENDACIÓN DE PRODUCTOS 1     | RECOMENDACIÓN DE PRODUCTOS 2 |
|----------------------------------|------------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b>    |

Comprobar cada cada 500 km, cambiar cada cada 12 meses

## SERVODIRECCIÓN

Capacidad: 1,3 litro

| USO    | CLIMA    |
|--------|----------|
| Normal | Templado |

| RECOMENDACIÓN DE PRODUCTOS 1 | RECOMENDACIÓN DE PRODUCTOS 2 |
|------------------------------|------------------------------|
| <b>ATF Dexron II-D</b>       |                              |

Comprobar cada cada 500 km

**ALFA ROMEO (EU) 145 930 145 1.4 (1994-1997)****SISTEMA DE REFRIGERACIÓN**

Capacidad: 8,4 litro

| USO                          |  | CLIMA    |
|------------------------------|--|----------|
| Normal                       |  | Templado |
| RECOMENDACIÓN DE PRODUCTOS 1 |  |          |
| Coolant -38 Organic NF       |  |          |

*Comprobar cada cada 500 km, cambiar cada cada 60000 km/ 24 meses*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*