

ALFA ROMEO (EU) 156 932 156 2.4 JTD 20V (120 KW) (2003-2005)



MOTOR 841M000
Capacidad: 5 litro

USO	CLIMA
Normal	Templado

RECOMENDACIÓN DE PRODUCTOS 1

Emperol 5W-40

Cambiar cada cada 20000 km

TRANSMISIÓN 'TRANSAXLE' MANUAL 5/1
Capacidad: 3,1 litro

USO	CLIMA
Normal	Templado

RECOMENDACIÓN DE PRODUCTOS 1

SP Gear 1071

RECOMENDACIÓN DE PRODUCTOS 2

Syngear 75W-90

Comprobar cada cada 80000 km

SISTEMA HIDRÁULICO FRENOS Y EMBRAGUE
Capacidad: 0,5 litro

USO	CLIMA
Normal	Templado

RECOMENDACIÓN DE PRODUCTOS 1

Drauliquid-LV Super DOT 4

RECOMENDACIÓN DE PRODUCTOS 2

Drauliquid-S DOT 4

Comprobar cada cada 500 km, cambiar cada cada 60000 km/ 24 meses

SERVODIRECCIÓN
Capacidad: 1,3 litro

USO	CLIMA
Normal	Templado

RECOMENDACIÓN DE PRODUCTOS 1

ATF Dexron II-D

Comprobar cada cada 20000 km

SISTEMA DE REFRIGERACIÓN
Capacidad: 7,25 litro

USO	CLIMA
Normal	Templado

RECOMENDACIÓN DE PRODUCTOS 1

Coolant -38 Organic NF

Comprobar cada cada 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

RECOMENDACIÓN DE PRODUCTOS

ALFA ROMEO (EU) 156 932 156 2.4 JTD 20V (120 KW) (2003-2005)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.