

# ALFA ROMEO (EU) 156 932 156 3.2 V6 GTA (2002-2005)

**ENGINE** 932A000

Capacity: 5,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Emperol Racing 10W-60***Check every 500 km, change every 20000 km/ 12 months***TRANSAXLE MANUAL** 6/1

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Syngear 75W-90***Check every 80000 km/ 48 months***SELESPEED** Selespeed

Capacity: 0,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Fluid 3023***Check every 20000 km/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

Capacity: 0,53 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 20000 km/ 12 months, change every 60000 km/ 24 months***POWER STEERING**

Capacity: 1,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 20000 km/ 12 months*

# ALFA ROMEO (EU) 156 932 156 3.2 V6 GTA (2002-2005)

**COOLING SYSTEM**

Capacity: 9,2 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| Coolant -38 Organic NF   |  |          |

*Check every 20000 km/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*