

# ALFA ROMEO (EU) 159 939 159 3.2 JTS Q4 (2005-2010)



**ENGINE** 939A000  
Capacity: 5,4 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Emperol 5W-40**

Check every 3000 km, change every 30000 km/ 24 months

**DIFFERENTIAL REAR**  
Capacity: 0,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071**

PRODUCT RECOMMENDATION 2

**Syngear 75W-90**

Check every 24 months/ 30000 km

**TRANSAXLE AUTOMATIC** Aisin Warner AF 40-6 6/1  
Capacity: 6,1 liter (Dry fill), Capacity: 3,3 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4026**

Check every 30000 km

**TRANSAXLE MANUAL** 6/1  
Capacity: 2,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 5015**

**TRANSFERBOX**  
Capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071**

PRODUCT RECOMMENDATION 2

**Syngear 75W-90**

Check every 30000 km/ 24 months, change every 120000 km

# ALFA ROMEO (EU) 159 939 159 3.2 JTS Q4 (2005-2010)



## HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Change every 30000 km/ 24 months

## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

Check every 24 months/ 30000 km

## GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE

Capacity: 115 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

## GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE

Capacity: 151 grams

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

## COOLING SYSTEM

Capacity: 10,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 24 months/ 30000 km

## AIRCONDITIONING COMPRESSOR

Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.