

**ASTON MARTIN DBS DBS V12 (2009-2011)****ENGINE**

Capacity: 11 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Helar 0W-40***Change every 16000 km/ 12 months***DIFFERENTIAL FROM AUTOMATIC**

Capacity: 1,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 5015***Change every 32000 km/ 24 months***TRANSAXLE MANUAL** Graziano 6/1

Capacity: 5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 5015***Check every 32000 km/ 24 months, change every 64000 km/ 48 months***TRANSMISSION AUTOMATIC** ZF 6HP26 6/1

Capacity: 9,7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 4026***Check every 16000 km/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-S DOT 4***Check every 16000 km, change every 12 months*

**ASTON MARTIN DBS DBS V12 (2009-2011)****POWER STEERING**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Fluid 3013**

Check every 16000 km/ 12 months

**COOLING SYSTEM**

Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF**

Check every 16000 km/ 12 months, change every 160000 km/ 60 months

**AIRCONDITIONING**

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*