PRODUCT RECOMMENDATION

# AUDI (EU) A3, S3 8L A3 1.8 20V TURBO (110 KW) (1996-2000)

## ENGINE AGU, AQA, ARX, ARZ, AUM
Capacity: 4,5 liter, Filter capacity: 0,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Helar SP LL-03 0W-30** | **Helar SP LL-03 5W-30** | **Helar 0W-40** |

*Change every 15000 km/ 12 months*

| USE | CLIMATE |
|---|---|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Presteza MSP 5W-30** | | |

*Change every 15000 km/ 12 months*

## DIFFERENTIAL FROM AUTOMATIC
Capacity: 0,75 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Gear 1011** | **Syngear TDL 75W-90** | |

*Check every 60000 km*

## TRANSAXLE MANUAL 02J 5/1
Capacity: 2 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **SP Gear 1081** | | |

*Check every 30000 km*

## TRANSMISSION AUTOMATIC 01M 4/1
Capacity: 5,3 liter (Initial fill), Capacity: 3 liter (Service fill)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Matic 4026** | **SP Matic 2032** | |

*Check every 30000 km, change every 60000 km/ 48 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# AUDI (EU) A3, S3 8L A3 1.8 20V TURBO (110 KW) (1996-2000)

## HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |
| *Change every 24 months* | | |

## POWER STEERING

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **SP Fluid 3013** | | |

## COOLING SYSTEM

Capacity: 5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Coolant SP 12** | **Coolant SP 12 EVO** | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367