

AUDI (EU) A4, S4, RS 4 8K A4 1.8 TFSI QUATTRO (118 KW) (2007-2012)



ENGINE CABB, CDHB
Capacity: 4,6 liter

USE

Extended drain (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar SP LL-03 5W-30**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!
Change every 30000 km/ 24 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar 0W-40****PRODUCT RECOMMENDATION 2****Emperol 5W-40****PRODUCT RECOMMENDATION 3****Asyntho 5W-30**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!
Change every 15000 km/ 12 months*

DIFFERENTIAL REAR 0BC
Capacity: 0,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!
Check every 24 months/ 30000 km*

TRANSAXLE MANUAL/TRANSFERBOX 0B2 6/1
Capacity: 4,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!
Check every 24 months/ 30000 km*

AUDI (EU) A4, S4, RS 4 8K A4 1.8 TFSI QUATTRO (118 KW) (2007-2012)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!
Change every 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!
Check every 24 months/ 30000 km

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!
Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.