

PRODUCT RECOMMENDATION

# AUDI (EU) A4, S4, RS 4 8K A4 3.0 TDI QUATTRO (176 KW) (2009-2012)



**ENGINE** CCWA, CCLA  
Capacity: 6,9 liter

**USE**

Extended drain (max)

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1**

**Helar SP LL-03 0W-30**

**PRODUCT RECOMMENDATION 2**

**Helar SP LL-03 5W-30**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!  
Change every 30000 km/ 24 months*

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1**

**Helar SP LL-03 0W-30**

**PRODUCT RECOMMENDATION 2**

**Helar SP LL-03 5W-30**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!  
Change every 15000 km/ 12 months*

## DIFFERENTIAL REAR

Capacity: 0,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1**

**SP Gear 1011**

**PRODUCT RECOMMENDATION 2**

**Syngear TDL 75W-90**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!  
Check every 24 months/ 30000 km*

## DIFFERENTIAL REAR ACTUATION

Capacity: 0,85 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1**

**SP Gear 1081**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*

# AUDI (EU) A4, S4, RS 4 8K A4 3.0 TDI QUATTRO (176 KW) (2009-2012)


**TRANSAXLE MANUAL/TRANSFERBOX 0B4 6/1**

Capacity: 3,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	

Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!  
Check every 24 months/ 30000 km

**TRANSMISSION S TRONIC CLUTCH PART 0B5 (DL501)**

Capacity: 7,5 liter (Dry fill, with oil cooler), Capacity: 7 liter (Dry fill, without oil cooler), Capacity: 6,7 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2072</b>		

Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!

**TRANSMISSION S TRONIC TRANSMISSION PART 0B5 (DL501) 7/1**

Capacity: 4,35 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2072</b>		

Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!

**TRANSMISSION S TRONIC TRANSMISSION PART 0B5 (DL501) NWD, NWF, NVZ 7/1**

Capacity: 4,35 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2072</b>		

Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!

# AUDI (EU) A4, S4, RS 4 8K A4 3.0 TDI QUATTRO (176 KW) (2009-2012)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*  
*Change every 24 months*

## POWER STEERING

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**SP Fluid 3013**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*  
*Check every 24 months/ 30000 km*

## COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Coolant SP 12 EVO**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*  
*Check every 24 months/ 30000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*