AUDI (EU) A5, S5, RS 5 8T A5 2.0 TFSI (169 KW) (2015-2016)



Capacity: 4,6 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar SP LL-03 5W-30		
Change every 30000 km/ 24 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Change every 15000 km/ 12 months

DIFFERENTIAL CVT Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

TRANSAXLE MANUAL 0B1 6/1 Capacity: 4 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 SP Gear 5015	
	!

Check every 24 months/ 30000 km

TRANSMISSION CVT 0AW 1/1 Capacity: 8 liter (Dry fill), Capacity: 5,5-6 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4016		
Change every 60000 km		

AUDI (EU) A5, S5, RS 5 8T A5 2.0 TFSI (169 KW) (2015-2016)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	q	CLIMATE
Normal	l I	Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
	· · · · · · · · · · · · · · · · · · ·	

Change every 24 months

COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Check every 24 months/ 30000 km	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.