AMMANN RUBBER TYRED ROLLERS AP AP 240 H CUMMINS 4BT4.5-C99 T3 (2006-2042)



2012)

ENGINE Cummins BT4.5-C99 Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Check every 20 hours, change every 3 months/ 250 hours

WHEEL GEARS Capacity: 2,5 liter (each side)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
011	10 11 / 1500 /	

Check every 20 hours, change every 12 months/ 1500 hours

HYDRAULIC CIRCUIT TRAVEL AND ST Capacity: 75 liter	EERING	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	
Check every 20 hours, change every 24 m	onths/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Check every 20 hours, change every 24 m	nonths/ 2000 hours	

CLIMATE
Moderate
PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION

AMMANN RUBBER TYRED ROLLERS AP AP 240 H CUMMINS 4BT4.5-C99 T3 (2006-



2012)

COOLING SYSTEM Capacity: 20,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 20 hours, change eve	ery 24 months/2000 hours	·

Check every 20 hours, change every 24 months/ 2000 hours

HYDRAULIC CILINDERS FRONT AXLE			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 46	Perlus H 68		
Check every 20 hours, change every 24 n	nonths/ 2000 hours		
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Perlus H 32			
Check every 20 hours, change every 24 n	nonths/ 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.