

AMMANN SINGLE DRUM ROLLERS ASC

ASC 200 HTPD CUMMINS TIER 3



ENGINE Cummins QSB6.7-C220
Capacity: 19,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Check every 20 hours, change every 6 months/ 500 hours

TRANSMISSION DRUM DRIVE
Capacity: 7,7 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Change every 100 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 hours

AMMANN SINGLE DRUM ROLLERS ASC

ASC 200 HTPD CUMMINS TIER 3



WHEEL GEARS

Capacity: 4,4 liter (each)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube HS GL-5 80W-140*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Gearlube HS GL-5 80W-140*Change every 100 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 100 hours*

HYDRAULIC SYSTEM

Capacity: 100 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 68*Check every 20 hours, change every 24 months/ 2000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Perlus H 32*Check every 20 hours, change every 24 months/ 2000 hours*

AMMANN SINGLE DRUM ROLLERS ASC

ASC 200 HTPD CUMMINS TIER 3



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

Change every 250 hours/ 3 months

COOLING SYSTEM

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 20 hours, change every 24 months/ 2000 hours

VIBRATORY DRUM FRONT

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Check every 250 hours/ 3 months, change every 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.