## **AMMANN HEAVY LINE PLATES AVH AVH 100-20 FARYMANN 43F** (1998 AND AFTER)



ENGINE Farymann 43F Capacity: 2,1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 250 hours/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40
Change every 250 hours/ 12 months	<u>'</u>	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 25 hours		
USE		CLIMATE
use Initial service		climate Moderate
	PRODUCT RECOMMENDATION 2	
Initial service	PRODUCT RECOMMENDATION 2 Kroontrak MTH 10W-30	Moderate
Initial service PRODUCT RECOMMENDATION 1		Moderate  PRODUCT RECOMMENDATION 3
Initial service PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40		Moderate  PRODUCT RECOMMENDATION 3
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM		Moderate  PRODUCT RECOMMENDATION 3
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM Capacity: 27 liter		Moderate  PRODUCT RECOMMENDATION 3  Synfleet SHPD 10W-40
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM		Moderate  PRODUCT RECOMMENDATION 3
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM Capacity: 27 liter  USE		Moderate  PRODUCT RECOMMENDATION 3  Synfleet SHPD 10W-40  CLIMATE
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM Capacity: 27 liter  USE Normal		Moderate  PRODUCT RECOMMENDATION 3  Synfleet SHPD 10W-40  CLIMATE
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM Capacity: 27 liter  USE Normal  PRODUCT RECOMMENDATION 1		Moderate  PRODUCT RECOMMENDATION 3  Synfleet SHPD 10W-40  CLIMATE
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM Capacity: 27 liter  USE Normal  PRODUCT RECOMMENDATION 1  Perlus H 32		Moderate  PRODUCT RECOMMENDATION 3  Synfleet SHPD 10W-40  CLIMATE
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM Capacity: 27 liter  USE Normal  PRODUCT RECOMMENDATION 1  Perlus H 32  Change every 1000 hours/ 12 months		Moderate  PRODUCT RECOMMENDATION 3  Synfleet SHPD 10W-40  CLIMATE  Moderate
Initial service  PRODUCT RECOMMENDATION 1  Kroontrak CVT 10W-40  Change every 25 hours  HYDRAULIC SYSTEM Capacity: 27 liter  USE Normal  PRODUCT RECOMMENDATION 1  Perlus H 32  Change every 1000 hours/ 12 months  USE		Moderate  PRODUCT RECOMMENDATION 3  Synfleet SHPD 10W-40  CLIMATE  Moderate  CLIMATE

Change every 500 hours

## AMMANN HEAVY LINE PLATES AVH AVH 100-20 FARYMANN 43F (1998 AND AFTER)



VIBRATOR UNIT Capacity: 2,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	
Change every 250 hours/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.