

ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change every 500 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 1000 hours	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	

Gearlube LS 80W-90

Change every 1000 hours

USE	CLIMATE
Initial service	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 500 hours	

Onange every 500 nours	
USE	CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Change every 500 hours



PLANETARY GEARS	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 1000 hours	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours	
USE	CLIMATE
Initial service	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 500 hours	
USE	CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	



TRANSMISSION ZF		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Multifleet SCD 20W-20	
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 2000 hours		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Multifleet SCD 20W-20	
Change every 500 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 500 hours		·
HYDRAULIC SYSTEM		

USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 20W-20	
Change every 3000 hours	
USE	CLIMATE
Normal	Cald

Normal	Cold
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 3000 hours	



GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	
Change avery 2000 hours	

Change every 2000 hours

SWING REDUCTION UNIT	
use Normal	climate Tropical
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	

Change every 1000 hours

use Normal	сымате Mediterranean	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1000 hours		

Change every 1000 hours

SWING RING GEAR TEETH		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Compound OGL EP 0/1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.