AUSA FORKLIFT TRUCKS C 200 H (4X2) ISUZU 4LE2 TIER 2 (2006 AND AFTER)



Normal PRODUCT RECOMMENDATION 1		Mediterranean
PRODUCT RECOMMENDATION 1		
	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SHPD 20W-50
Change every 12 months/ 150 hours		·
JSE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40
Change every 12 months/ 150 hours		·
JSE		CLIMATE
nitial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SHPD 20W-50
Change every 50 hours		
JSE		CLIMATE
nitial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40
Change every 50 hours	:	.

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 40 hours, change every 1	2 months/ 600 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 50 hours		

AUSA FORKLIFT TRUCKS C 200 H (4X2) ISUZU 4LE2 TIER 2 (2006 AND AFTER)



HUB REDUCTIONS FRONT Capacity: 0,41 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 40 hours, change every 12 m	onths/ 600 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 50 hours		

CLIMATE
Moderate
ATION 2
s/GL-5 80W-90

Check every 40 hours, change every 12 months/ 600 hours

JSE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Check every 40 hours, change eve	ry 900 hours	
JSE		CLIMATE
nitial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

AUSA FORKLIFT TRUCKS C 200 H (4X2) ISUZU 4LE2 TIER 2 (2006 AND AFTER)



HYDRAULIC SYSTEM BRAKING & Capacity: 0,9 liter	RINCHING	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30
Check every 40 hours, change ever	v 12 months/ 900 hours	

Check every 40 hours, change every 12 months/ 900 hours

information contained herein is subject to changes without notification.

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 6,82 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 40 hours, change every	24 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

KROON-OIL B.V. Postbus 149 7600 AC Almelo