

AUSA FORKLIFT TRUCKS C 200 H (4X4)

KUBOTA V2003T (2006 AND AFTER)



ENGINE Kubota V2003-T
Capacity: 7,9 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 20W-50

Change every 12 months/ 150 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40

Change every 12 months/ 150 hours

USE
Initial service

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 20W-50

Change every 50 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40

Change every 50 hours

DIFFERENTIAL FRONT
Capacity: 4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube LS 80W-90

Check every 40 hours, change every 12 months/ 600 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube LS 80W-90

Change every 50 hours

AUSA FORKLIFT TRUCKS C 200 H (4X4)

KUBOTA V2003T (2006 AND AFTER)

**DIFFERENTIAL REAR**

Capacity: 3,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 40 hours, change every 12 months/ 600 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

HUB REDUCTIONS FRONT

Capacity: 0,4 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 40 hours, change every 12 months/ 600 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 50 hours

HUB REDUCTIONS REAR

Capacity: 0,3 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 40 hours, change every 12 months/ 600 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

AUSA FORKLIFT TRUCKS C 200 H (4X4)

KUBOTA V2003T (2006 AND AFTER)



TRANSFERBOX Compen
Capacity: 2,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 40 hours, change every 12 months/ 600 hours

HYDRAULIC SYSTEM

Capacity: 45 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Perlus AF 100

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 68

PRODUCT RECOMMENDATION 2

Perlus AF 68

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus AF 46

HYDRAULIC SYSTEM BRAKING & INCHING

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

Check every 40 hours, change every 12 months/ 900 hours

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

AUSA FORKLIFT TRUCKS C 200 H (4X4)

KUBOTA V2003T (2006 AND AFTER)

**COOLING SYSTEM**

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 40 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.