

# BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25L (4X4) DEUTZ F10L413FW



**ENGINE** Deutz F10L-413FW  
Capacity: 15 liter, Filter capacity: 1,5 liter

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Mediterranean

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SCD 30**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

*Change every 100 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SCD 30**

*Change every 100 hours*

# BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25L (4X4) DEUTZ F10L413FW



USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 100 hours*

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		

*Change every 100 hours*

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 100 hours*

## DIFFERENTIAL FRONT Bell

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 250 hours, change every 500 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 100 hours*



# BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25L (4X4) DEUTZ F10L413FW

**DIFFERENTIAL REAR Bell**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Check every 250 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 100 hours*

**DIFFERENTIAL REAR ZF AP 17-R**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Check every 250 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 100 hours*

**FINAL DRIVES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Check every 250 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 100 hours*

**TRANSMISSION ZF 6WG200 6/3**

Capacity: 28 liter

# BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25L (4X4) DEUTZ F10L413FW



USE Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 <b>Dieselfleet CD+ 15W-40</b>	PRODUCT RECOMMENDATION 2 <b>Multifleet SHPD 15W-40</b>	
<i>Check every 250 hours, change every 1000 hours</i>		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Kroontrak MTH 10W-30</b>	PRODUCT RECOMMENDATION 2 <b>Synfleet SHPD 10W-40</b>	PRODUCT RECOMMENDATION 3 <b>Multifleet SHPD 10W-40</b>
<i>Check every 250 hours, change every 1000 hours</i>		
USE Normal		CLIMATE Cold
PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 20W-20</b>	PRODUCT RECOMMENDATION 2 <b>HDX 20W-20</b>	
<i>Check every 250 hours, change every 1000 hours</i>		
USE Normal		CLIMATE Arctic
PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 10W</b>	PRODUCT RECOMMENDATION 2 <b>HDX 10W</b>	PRODUCT RECOMMENDATION 3 <b>ATF Almirol</b>
<i>Check every 250 hours, change every 1000 hours</i>		
USE Initial service		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 <b>Dieselfleet CD+ 15W-40</b>	PRODUCT RECOMMENDATION 2 <b>Multifleet SHPD 15W-40</b>	
<i>Change every 100 hours</i>		
USE Initial service		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Kroontrak MTH 10W-30</b>	PRODUCT RECOMMENDATION 2 <b>Synfleet SHPD 10W-40</b>	PRODUCT RECOMMENDATION 3 <b>Multifleet SHPD 10W-40</b>
<i>Change every 100 hours</i>		
USE Initial service		CLIMATE Cold
PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 20W-20</b>	PRODUCT RECOMMENDATION 2 <b>HDX 20W-20</b>	
<i>Change every 100 hours</i>		

# BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25L (4X4) DEUTZ F10L413FW



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 10W</b>	<b>HDX 10W</b>	<b>ATF Almirol</b>
<i>Change every 100 hours</i>		

HYDRAULIC SYSTEM		
Capacity: 230 liter (Hydraulic system including tank), Capacity: 175 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus H 68</b>	
<i>Change every 2000 hours</i>		

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		
<i>Change every 4000 hours</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.