BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B30L MK III (4X4) CUMMINS QSM11



ENGINE Cummins QSM11 Capacity: 37 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet CD+ 15W-40

Change every 250 hours/ 6 months

DIFFERENTIAL FRONT Bell		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 1000 hours, change every 2000 hours		

DIFFERENTIAL REAR Bell	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
Check every 1000 hours, change every 2000 hours	·

TRANSMISSION ZF 6WG210 6/3 Capacity: 26 liter (Dry fill), Capacity: 16 liter (Service fill)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Change every 1000 hours	·	

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B30L MK III (4X4) CUMMINS QSM11



HYDRAULIC SYSTEM Capacity: 140 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	Perlus H 32
Change every 2000 hours	All Allinoi	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 86 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 2000 hours		·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.