

BELL EQUIPMENT ARTICULATED TRUCKS & HAULERS 2306D MK VI (4X4) MERCEDES- BENZ OM906LA (2007 AND AFTER)



ENGINE Mercedes-Benz OM906LA
Capacity: 29 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth 10W-40

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT Bell 14T
Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 2000 hours

DIFFERENTIAL REAR Bell 14T
Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 2000 hours

HUB REDUCTIONS FRONT
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 2000 hours

HUB REDUCTIONS REAR
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 2000 hours

BELL EQUIPMENT ARTICULATED TRUCKS & HAULERS 2306D MK VI (4X4) MERCEDES- BENZ OM906LA (2007 AND AFTER)

**TRANSFERBOX VGR 13200**

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours***TRANSMISSION ZF HP592C**

Capacity: 30 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours***HYDRAULIC SYSTEM**

Capacity: 70 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

Multifleet SCD 10W*Change every 4000 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2**COOLING SYSTEM**

Capacity: 28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Change every 2000 hours*

BELL EQUIPMENT ARTICULATED TRUCKS & HAULERS 2306D MK VI (4X4) MERCEDES- BENZ OM906LA (2007 AND AFTER)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.