PRODUCT RECOMMENDATION

BELL EQUIPMENT WHEELED LOADERS L L1204C PLUS II JOHN DEERE 4045TF250 (TIER I)

ENGINE John Deere 4045 TF250
Capacity: 13,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Change every 250 hours/ 6 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**
Change every 250 hours/ 6 months		

DIFFERENTIAL FRONT ZF MT-L3075
Capacity: 24,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 1000 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1000 hours		

DIFFERENTIAL REAR ZF MT-L3065
Capacity: 24 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 1000 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1000 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BELL EQUIPMENT WHEELED LOADERS L L1204C PLUS II JOHN DEERE 4045TF250 (TIER I)

TRANSMISSION Clark 24000 4/3
Capacity: 25 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gear Oil Alcat 10W	**SP Matic 2032**	**ATF Dexron II-D**

Change every 1000 hours

TRANSMISSION ZF 4WG130 4/3
Capacity: 26 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**SP Matic 2032**

Change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 120 liter (Hydraulic system including tank), Capacity: 100 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	**Multifleet SCD 10W**	

Change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BELL EQUIPMENT WHEELED LOADERS L L1204C PLUS II JOHN DEERE 4045TF250 (TIER I)

COOLING SYSTEM
Capacity: 30 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367