

# BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T12B MKII (6X6 FORWARDER) CUMMINS 4BTA 3.9C

**ENGINE** Cummins 4BTA3.9C

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Multifleet SCD 40</b> | <b>Multifleet SCD 30</b> |  |

*Change every 250 hours/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-----------------------------|--------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Asyntho 5W-30</b>     |

*Change every 250 hours/ 6 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Multifleet SCD 10W</b> |  |  |

*Change every 250 hours/ 6 months*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Multifleet SCD 40</b> | <b>Multifleet SCD 30</b> |  |

*Change every 100 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-----------------------------|--------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Asyntho 5W-30</b>     |

*Change every 100 hours*

| USE             | CLIMATE |
|-----------------|---------|
| Initial service | Cold    |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Multifleet SCD 10W</b> |  |  |

*Change every 100 hours*

# BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T12B MKII (6X6 FORWARDER) CUMMINS 4BTA 3.9C



## DIFFERENTIAL FRONT Bell 14T

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Check every 250 hours, change every 500 hours

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Change every 100 hours

## DIFFERENTIAL REAR (TANDEM BOGIE) Clark-Hurth

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1           |  |  |
|------------------------------------|--|--|
| <b>Unigear HS GL-3/GL-5 80W-90</b> |  |  |

Check every 250 hours, change every 1000 hours

## FINAL DRIVES FRONT

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Change every 500 hours

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Change every 100 hours

## HUB REDUCTIONS REAR (TANDEM BOGIE)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1           |  |  |
|------------------------------------|--|--|
| <b>Unigear HS GL-3/GL-5 80W-90</b> |  |  |

Check every 250 hours, change every 2000 hours

# BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T12B MKII (6X6 FORWARDER) CUMMINS 4BTA 3.9C



## TRANSMISSION Clark 18000 3/3

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Check every 250 hours, change every 1000 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

PRODUCT RECOMMENDATION 2

**ATF Dexron II-D***Check every 250 hours, change every 1000 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 100 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

PRODUCT RECOMMENDATION 2

**ATF Dexron II-D***Change every 100 hours*

## HYDRAULIC SYSTEM

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 68**

PRODUCT RECOMMENDATION 3

**Perlus AF 46**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**ATF-A**

PRODUCT RECOMMENDATION 2

**Perlus H 32**

PRODUCT RECOMMENDATION 3

**Perlus AF 32**

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

# BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T12B MKII (6X6 FORWARDER) CUMMINS 4BTA 3.9C



## COOLING SYSTEM

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*