

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1226A JOHN DEERE 6068TF150



ENGINE John Deere 6068 TF150
Capacity: 19 liter

USE Normal	CLIMATE Moderate
---------------	---------------------

PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40	PRODUCT RECOMMENDATION 3 Agridiesel MSP 15W-40
---	---	--

Change every 250 hours/ 6 months

USE Initial service	CLIMATE Moderate
------------------------	---------------------

PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40	PRODUCT RECOMMENDATION 3 Agridiesel MSP 15W-40
---	---	--

Change every 100 hours

DIFFERENTIAL REAR
Capacity: 32 liter

USE Normal	CLIMATE Mediterranean
---------------	--------------------------

PRODUCT RECOMMENDATION 1 Gearlube Racing 75W-140	PRODUCT RECOMMENDATION 2 Unigear LS GL-3/GL-5 85W-140	
--	---	--

Check every 250 hours, change every 2000 hours

USE Normal	CLIMATE Moderate
---------------	---------------------

PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90		
---	--	--

Check every 250 hours, change every 2000 hours

TRANSMISSION Allison 2500 TC210 6/1
Capacity: 14 liter (Dry fill)

USE Normal	CLIMATE Moderate
---------------	---------------------

PRODUCT RECOMMENDATION 1 SP Matic 2032		
--	--	--

Check every 250 hours, change every 2000 hours

HYDRAULIC SYSTEM

Capacity: 147 liter (Hydraulic system including tank)

We are unable to give a standard recommendation for this component. Please contact our service department.



BELL EQUIPMENT RIGID TRACTORS & HAULERS 1226A JOHN DEERE 6068TF150



GREASE POINTS/NIPPLES WHEEL BEARINGS + DRIVE TRAIN

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 22 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Coolant SP 15+	PRODUCT RECOMMENDATION 2 Coolant SP 12	PRODUCT RECOMMENDATION 3 Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.