

BOBCAT EXCAVATORS 341 (1999-2003)

ENGINE Kubota V2003-MT
Capacity: 7,1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|--------------------------|--|
| Multifleet SHPD 20W-50 | Multifleet SCD 40 | |

Check every 10 hours, change every 500 hours/ 6 months

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Multifleet SCD 30 | | |

Check every 10 hours, change every 500 hours/ 6 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |

Check every 10 hours, change every 500 hours/ 6 months

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Multifleet SCD 10W | | |

Check every 10 hours, change every 500 hours/ 6 months

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Tropical |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|--------------------------|--|
| Multifleet SHPD 20W-50 | Multifleet SCD 40 | |

Check every 10 hours, change every 50 hours

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Multifleet SCD 30 | | |

Check every 10 hours, change every 50 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |

Check every 10 hours, change every 50 hours

BOBCAT EXCAVATORS 341 (1999-2003)

| USE | | CLIMATE |
|--|--|---------|
| Initial service | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| <i>Check every 10 hours, change every 50 hours</i> | | |

| TRAVEL REDUCTION UNIT COMBINED WITH HYDRAULIC SYSTEM | | |
|---|--|---------------|
| Capacity: 1,6 liter | | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus AF 100 | | |
| <i>Check every 250 hours, change every 6 months/ 1000 hours</i> | | |

| USE | | CLIMATE |
|---|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Perlus H 46 | Perlus H 68 | Perlus AF 46 |
| <i>Check every 250 hours, change every 6 months/ 1000 hours</i> | | |

| USE | | CLIMATE |
|---|--------------------------|----------|
| Acceptable | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Kroontrak MTH 10W-30 | HDX 10W | |
| <i>Check every 250 hours, change every 6 months/ 1000 hours</i> | | |

| TRAVEL REDUCTION UNIT SEPARATE LUBRICATION | | |
|---|------------------------------------|----------|
| Capacity: 1,6 liter | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| <i>Check every 250 hours, change every 6 months/ 1000 hours</i> | | |

| HYDRAULIC SYSTEM | | |
|--|--|---------------|
| Capacity: 22,7 liter (Hydraulic tank), Capacity: 62,5 liter (System) | | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus AF 100 | | |
| <i>Check every 10 hours, change every 6 months/ 1000 hours</i> | | |

BOBCAT EXCAVATORS 341 (1999-2003)

| | | |
|--|--|---|
| USE Normal | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Perlus H 46 | PRODUCT RECOMMENDATION 2 Perlus H 68 | PRODUCT RECOMMENDATION 3 Perlus AF 46 |
| <i>Check every 10 hours, change every 6 months/ 1000 hours</i> | | |
| USE Initial service | | CLIMATE Mediterranean |
| PRODUCT RECOMMENDATION 1 Perlus AF 100 | | |
| <i>Check every 10 hours, change every 6 months/ 100 hours</i> | | |
| USE Initial service | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Perlus H 46 | PRODUCT RECOMMENDATION 2 Perlus H 68 | PRODUCT RECOMMENDATION 3 Perlus AF 46 |
| <i>Check every 10 hours, change every 6 months/ 100 hours</i> | | |
| USE Alternative (acceptable) | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 | PRODUCT RECOMMENDATION 2 HDX 10W | |
| <i>Check every 10 hours, change every 6 months/ 1000 hours</i> | | |
| USE Initial service (alternative) | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 | PRODUCT RECOMMENDATION 2 HDX 10W | |
| <i>Check every 10 hours, change every 6 months/ 100 hours</i> | | |
| USE Biodegradable oil | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 | | |
| <i>Check every 10 hours, change every 6 months/ 1000 hours</i> | | |
| USE Initial service, biodegradable oil | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 | | |
| <i>Check every 10 hours, change every 6 months/ 100 hours</i> | | |

BOBCAT EXCAVATORS 341 (1999-2003)**GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 10 hours

COOLING SYSTEM

Capacity: 17 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 10 hours, change every 6 months/ 1000 hours

SWING DRIVE GEARBOX

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.