

BOBCAT SKID STEER LOADERS T320 H

KUBOTA V3800-DI-T (2008-2012)



ENGINE Kubota V3800-DI-T
Capacity: 11,4 liter

USE		CLIMATE
Normal, fuel sulfur level < 0,05 %		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

USE		CLIMATE
Normal, fuel sulfur level < 0,05 %		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

USE		CLIMATE
Normal, fuel sulfur level < 0,05 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Asyntho 5W-30	Dieselfleet CD+ 15W-40

USE		CLIMATE
Normal, fuel sulfur level < 0,05 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

HYDRAULIC SYSTEM
Capacity: 17,8 liter (Hydraulic tank), Capacity: 49,2 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

COOLING SYSTEM
Capacity: 17,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -33 MPG		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

BOBCAT SKID STEER LOADERS T320 H

KUBOTA V3800-DI-T (2008-2012)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.