

# CASE WHEELED LOADERS 921C XR

## CUMMINS QSM11 (1999-2008)



**ENGINE** Cummins QSM11  
Capacity: 36,9 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Change every 250 hours*

### DIFFERENTIAL FRONT

Capacity: 36,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### DIFFERENTIAL REAR

Capacity: 36,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### HUB REDUCTIONS

Capacity: 13,6 liter (each hub)

We are unable to give a standard recommendation for this component. Please contact our service department.

### TRANSMISSION POWERSHIFT ZF 4/3

Capacity: 28,4 liter (Change capacity), Capacity: 46 liter (Dry fill)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

*Check every 50 hours, change every 1000 hours*

USE  
First change only

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

*Check every 50 hours, change every 100 hours*

### HYDRAULIC SYSTEM

Capacity: 125 liter (Hydraulic tank), Capacity: 242 liter (Total)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

*Check every 50 hours, change every 2000 hours*

# CASE WHEELED LOADERS 921C XR

## CUMMINS QSM11 (1999-2008)

**COOLING SYSTEM**

Capacity: 57 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26**

*Check every 10 hours, change every 2000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*