PRODUCT RECOMMENDATION

CASE MINI EXCAVATORS CK/CX CK50



ENGINE Kubota		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every 6 m	nonths/ 100 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change every 6 m	nonths/ 100 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Check every 10 hours, change every 6 m	nonths/ 100 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every 50	hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change every 50	hours	
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Check every 10 hours, change every 50	hours	

HYDRAULIC SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 46			
Check every 10 hours, change every 1000 hours			

KROON-OIL B.V. Postbus 149 7600 AC Almelo

CASE MINI EXCAVATORS CK/CX CK50



GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
MoS2 Grease EP 2				
Change every 10 hours				

 SWING REDUCTION UNIT

 Use
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2

 Gearlube GL-5 85W-140
 Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

SWING RING GEAR TEETH			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			
Change every 10 hours			

TRACK ROLLERS + IDLER WHEELS			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			

Change every 10 hours

TRAVEL REDUCTION UNIT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 1000 hours	•	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.