

# CASE SKID STEER LOADERS SV300 (2012-2017)



**ENGINE** Case 434T/E Tier 4  
Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Armado Synth 5W-30</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 10 hours, change every 250 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Armado Synth 5W-30</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Change every 50 hours*

**CHAIN DRIVE UNIT**  
Capacity: 27,9 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Armado Synth 5W-30</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 500 hours, change every 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 15 liter (Hydraulic tank), Capacity: 44,5 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Armado Synth 5W-30</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 10 hours, change every 1000 hours*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

*Change every 10 hours*

# CASE SKID STEER LOADERS SV300 (2012-2017)



## COOLING SYSTEM

Capacity: 19 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

## PRODUCT RECOMMENDATION 2

**Coolant -26***Check every 10 hours, change every 1000 hours*

## TRAVEL REDUCTION UNIT

Capacity: 1 liter (each)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

## PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140***Change every 500 hours*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

## PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140***Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.