

## CASE BACKHOE LOADERS 590 TURBO

**ENGINE**

Capacity: 11 liter

| USE                          |                               | CLIMATE                       |
|------------------------------|-------------------------------|-------------------------------|
| Normal                       |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 250 hours*

| USE                         |                               | CLIMATE |
|-----------------------------|-------------------------------|---------|
| Normal                      |                               | Cold    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |         |
| <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |         |

*Check every 10 hours, change every 250 hours***TRANSAXLE**

Capacity: 45 liter (Change capacity), Capacity: 54 liter (Total)

| USE                              |                          | CLIMATE                  |
|----------------------------------|--------------------------|--------------------------|
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |

*Check every 250 hours, change every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 79,5 liter (Hydraulic tank), Capacity: 128,7 liter (Total)

| USE                              |                          | CLIMATE  |
|----------------------------------|--------------------------|----------|
| Normal                           |                          | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |          |

*Check every 50 hours, change every 1000 hours*

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Biodegradable oil         |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Perlus Biosynth 46</b> |  |          |

*Check every 50 hours, change every 1000 hours*

## CASE BACKHOE LOADERS 590 TURBO



## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Change every 10 hours

## COOLING SYSTEM

Capacity: 17,8 liter, Capacity: 18,5 liter (+ heater)

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.