

# CATERPILLAR ARTICULATED DUMP TRUCKS D20D

**ENGINE**

Capacity: 25 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

PRODUCT RECOMMENDATION 2

**Multifleet SCD 30***Check every 10 hours, change every 1 months/ 250 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Synfleet SHPD 10W-40***Check every 10 hours, change every 1 months/ 250 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 10 hours, change every 1 months/ 250 hours***DIFFERENTIAL FRONT**

Capacity: 29 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Gearlube LS 80W-90***Check every 10 hours, change every 6 months/ 1000 hours***DIFFERENTIAL REAR**

Capacity: 29 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Gearlube LS 80W-90***Check every 10 hours, change every 6 months/ 1000 hours*

# CATERPILLAR ARTICULATED DUMP TRUCKS D20D



## TRANSMISSION

Capacity: 40 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |               |

Check every 10 hours, change every 6 months/ 1000 hours

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

Check every 10 hours, change every 6 months/ 1000 hours

## HYDRAULIC SYSTEM

Capacity: 150 liter

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 30</b> |  |               |

Check every 10 hours, change every 2000 hours/ 12 months

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

Check every 10 hours, change every 2000 hours/ 12 months

| USE                       |  | CLIMATE       |
|---------------------------|--|---------------|
| Biodegradable oil         |  | Mediterranean |
| PRODUCT RECOMMENDATION 1  |  |               |
| <b>Perlus Biosynth 46</b> |  |               |

Check every 10 hours, change every 2000 hours/ 12 months

## COOLING SYSTEM

Capacity: 35 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

Change every 24 months/ 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

# CATERPILLAR ARTICULATED DUMP TRUCKS D20D



*information contained herein is subject to changes without notification.*