

CATERPILLAR RIGID DUMP TRUCKS 777C



ENGINE 3508A
Capacity: 91 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL REAR
Capacity: 314 liter (+ hub reductions)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

CATERPILLAR RIGID DUMP TRUCKS 777C



FINAL DRIVES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*
TRANSMISSION Powershift
 Capacity: 95 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Check every 10 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 10 hours, change every 6 months/ 1000 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

CATERPILLAR RIGID DUMP TRUCKS 777C

**WHEEL BEARINGS FRONT**

Capacity: 4,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50*Check every 1 months/ 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 1 months/ 250 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 1 months/ 250 hours***COOLING SYSTEM**

Capacity: 221 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Check every 10 hours, change every 24 months/ 3000 hours***HOIST CONVERTER + BRAKE SYSTEM**

Capacity: 250 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Check every 10 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 10 hours, change every 6 months/ 1000 hours*

CATERPILLAR RIGID DUMP TRUCKS 777C

**HYDRAULIC SYSTEM STEERING**

Capacity: 83 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.