PRODUCT RECOMMENDATION

CATERPILLAR WHEELED LOADERS 930K RHN/CATERPILLAR C6.6 ACERT TIER 4I (2012 AND AFTER)

ENGINE C6.6 Acert
Capacity: 19,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth MSP 10W-40	**Dieselfleet MSP 15W-40**	

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	**Agridiesel MSP 15W-40**	**Dieselfleet LSP Ultra 10W-30**

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT
Capacity: 27 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR
Capacity: 27 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION
Capacity: 8,5 liter, Capacity: 11 liter (+ cooler)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 2000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR WHEELED LOADERS 930K RHN/CATERPILLAR C6.6 ACERT TIER 4I (2012 AND AFTER)

HYDRAULIC SYSTEM
Capacity: 90 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Agridiesel MSP 15W-40		

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM
Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 12000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367