

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB32B 422/469 (2013 AND AFTER)



ENGINE C1.5
Capacity: 6 liter

USE		CLIMATE
Fluid analysis, preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40

Check every 250 hours

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40

Check every 250 hours

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 500 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 22 liter (Hydraulic tank)

USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 18 months/ 3000 hours

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 12 months/ 500 hours

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB32B 422/469 (2013 AND AFTER)



USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Fluid analysis, alternative		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 12 months/ 500 hours

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Check every 12 months/ 500 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 3 months/ 250 hours



CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB32B 422/469 (2013 AND AFTER)

**COOLING SYSTEM**

Capacity: 10,5 liter

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 12 months, change every 72 months/ 12000 hours

USE		CLIMATE
Fluid analysis, initial (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 500 hours

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 3 months/ 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.